

32 226

## LADYLUX® L2

### SINGLE-HANDLE PULL DOWN KITCHEN FAUCET DUAL SPRAY 1.75 GPM

Pure Freude  
an Wasser






#### STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- 15 3/4" Faucet height
- 9" Aerator height
- 7 3/4" Faucet reach
- GROHE Magnetic Docking guarantees easy retraction and smooth docking of the spray head back to the starting position
- Pull-down dual spray: laminar spray and shower spray
- Automatic return to laminar spray
- Adjustable flow rate limiter
- 360° Swivel spout
- Nylon braided flex hoses
- GROHE QuickFix® rapid installation system
- 1.75gpm
- Compatible with GROHE Foot Control retro-fit set (30 310 000)



#### PRODUCT FEATURES:



-  GROHE SilkMove®
-  GROHE StarLight®
-  GROHE QuickFix®

#### CERTIFICATIONS:



- ADA
- CEC Certified
- Low Lead Certified
- Cal Green Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- N/A
- CSA B125.1
- ASME A112.18.1
- Complies with lead plumbing laws

#### AVAILABLE FINISHES:

- 32226003**  GROHE StarLight® Chrome
- 32226DC3**  SuperSteel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

Tel: 1.630.582.7711 Fax: 1.630.582.7722  
We reserve the right to make revisions without notice to product specifications.  
For the most current Specification Sheet, go to [www.grohe.us](http://www.grohe.us).  
12-18-2020

PART OF **LIXIL**

32 226

# LADYLUX® L2

## SINGLE-HANDLE PULL DOWN KITCHEN FAUCET DUAL SPRAY 1.75 GPM

Pure Freude  
an Wasser



### TECHNICAL DATA:

Product Height	16-9/16 in
Product Length	7-3/4 in
Product Width	5 in
Fitting Spout Height	10-1/8 in
Fitting Spout Reach	8-9/16 in
Fitting Handle Height	6-15/16 in
GPM (Min)-GPM (Max)	1.75 gal (US)/min
Fitting No of Holes Required	1

